

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application.

**Listing of Claims:**

1. (canceled)
2. (previously amended) The method of claim 3 wherein power output from the starter motor is regulated to meet existing and impending power demands by drive system auxiliary devices.
3. (previously amended) A method for reducing exhaust emissions during cold start of an internal combustion engine, the engine being coupled to a starter motor and an exhaust gas treatment device, comprising:
  - providing assist to the engine by the starter motor to meet a demanded power when a temperature of the exhaust gas treatment system is less than an operating temperature of the exhaust gas treatment device; and
  - operating the starter motor as a generator after the operating temperature of the exhaust gas treatment device has been reached.
4. (previously amended) The method of claim 6, further comprising: retarding spark timing of the engine.
5. (previously amended) The method of claim 6, further comprising: heating the exhaust gas treatment device by electric heater coupled to the exhaust gas treatment device.

6. (currently amended) A method for reducing exhaust emissions during cold start of an internal combustion engine, the engine being coupled to a starter motor and an exhaust gas treatment device, comprising:

providing assist to the engine by the starter motor to meet a demanded power ~~when~~ until a temperature of the exhaust gas treatment system is ~~less than~~ reaches an operating temperature of the exhaust gas treatment device; ~~and delaying a shifting operation of an automatic transmission coupled to the internal combustion engine.~~

7. (canceled)

8. (previously amended) The method of claim 10, further comprising: retarding spark timing of the engine.

9. (previously amended) The method of claim 10, further comprising: heating the exhaust gas treatment device by electric heater coupled to the exhaust gas treatment device.

10. (~~previously~~ currently amended) The method of claim 6, further comprising: A method for reducing exhaust emissions during cold start of an internal combustion engine, the engine being coupled to a starter motor and an exhaust gas treatment device, comprising:

~~—supplying fuel to the internal combustion engine when an engine rotational speed substantially exceeds idle speed; and~~

delaying a shifting operation of an automatic transmission coupled to the internal combustion engine.

11. (cancel)

12. (previously amended) The system of claim 14 wherein said electronic control unit causes spark timing of the engine to be retarded.

13. (previously amended) The system of claim 14 wherein said electronic control unit causes an electric heater coupled to the exhaust gas treatment device to heating the exhaust gas treatment device.

14. (currently amended) An engine system comprising:

an internal combustion engine;

a starter motor coupled to said engine;

an exhaust gas treatment device arranged in an engine exhaust of said engine; and

a control unit electronically coupled to said engine and said starter motor, said control unit causing said starter motor to provide power to reduce a power provided by said engine until said exhaust gas treatment device achieves an operating temperature. ~~wherein said electronic control unit delays a shifting operation of an automatic transmission coupled to the internal combustion engine.~~

15. (canceled)

16. (currently amended) The system of claim 14~~8~~ wherein said electronic control unit causes spark timing of the engine to be retarded.

17. (currently amended) The system of claim 14~~8~~ wherein said electronic control unit causes an electric heater coupled to the exhaust gas treatment device to heating the exhaust gas treatment device.

18. (canceled)

19. (currently added) The engine system of claim 14~~8~~ wherein said starter motor is an integrated starter generator.

20. (currently amended) The method of claim ~~6~~10, further comprising:  
discontinuing ~~operation of~~providing assist by the starter motor when a  
temperature of the exhaust treatment device exceeds a ~~predetermined~~said  
operating temperature.

21. (currently amended) The method of claim ~~20~~6 wherein said  
~~predetermined~~operating temperature is a temperature at which the exhaust  
treatment device becomes active.

22. (currently a amended) The method of claim ~~10~~6 wherein said starter  
motor is an integrated starter generator.

23. (currently amended) The method of claim 22, further comprising:  
operating said integrated starter generator as a generator when a temperature  
of the exhaust treatment device exceeds a ~~predetermined~~said operating  
temperature.

24. (currently amended) A method for reducing exhaust emissions during  
cold start of an internal combustion engine, the engine being coupled to a starter  
motor and an exhaust gas treatment device, comprising:

supplying rotational energy to the engine at rest by the starter  
motor;

providing fuel to the engine when an engine rotational speed  
substantially exceeds an idle speed; and

continuing to operate both the engine and the starter motor after  
fuel is provided to the engine until the exhaust gas treatment device  
reaches a predetermined temperature.

25. (previously amended) The method of claim 24 wherein said engine  
supplies a lesser amount of power than otherwise because of power supplied by  
the starter motor when both the engine and starter motor are operating.

26. (previously amended) The method of claim 24 wherein said operating both the engine and the starter motor has both the engine and the starter motor providing mechanical power.

27. (currently amended) The method of claim 24, further comprising: discontinuing operation of the starter motor when a temperature of the exhaust treatment device exceeds said predetermined temperature.

28. (currently amended) The method of claim 27 wherein said predetermined temperature is a temperature at which the exhaust treatment device becomes active.

29. (previously amended) The method of claim 24 wherein said starter motor is an integrated starter generator.

30. (currently amended) The method of claim 29, further comprising: operating said integrated starter generator as a generator when a temperature of the exhaust treatment device exceeds said predetermined temperature.

31. (previously amended) The method of claim 27 wherein when the starter motor operation is discontinued, the starter motor provides substantially no positive or negative torque.